



Pritt Bastelkleber

Technical Data Sheet v.2, January 2025

CHARACTERISTICS

- Solvent-free
- Color white, dried film transparent
- Washable
- Ideal for handicrafts
- Easy application bottle: dots, line or larger surface with thin film



APPLICATION FIELD

Adhesive for home, school and office.

- Cork
- Wood
- Plastic
- Felt
- Fabric
- Leather
- Paper
- Cardboard
- Styropor®
- Foam rubber
- Metal such as aluminium

Not suitable for:

- Sensitive fabrics such as silk and water-sensitive materials and plastics such as PE, PP, PTFE, etc.

INSTRUCTIONS FOR USE

Pretreatment

The substrate must be clean, dry, free of dust and grease. Smooth surfaces should be roughened (e.g. with sandpaper). Ideally, the adhesive surface should be cleaned with water and dried beforehand.

Application

Apply a thin layer of PRITT BASTELKLEBER onto one side, join and fix the pieces together. For high absorbent materials (e.g. wood, cardboard): apply PRITT BASTELKLEBER glue on both surfaces to be bonded and join them. A correction of the bonded materials is possible.

Close cap tightly after use.

The maximum bonding strength is reached after 24 hours.

* Drying time depends on material and climate

APPENDIX

Consumption and other information

Packaging

Article abbreviation

Container sizes

PAKC1

6 bottles of 50 grammes each

PAKC2

6 bottles of 100 grammes each

TECHNICAL DATA

Composition	Polyvinyl acetate dispersion
pH	5.5 - 7.5
Viscosity, mPas (6/23°C/20 rpm)	9.000 - 21.000
Shelf Life, at 20°C	12 months



LIMITATIONS

Storage

Keep tightly closed and store in a dry and cool place. Avoid temperatures below 5°C and above 35°C.

HEALTH AND SAFETY

It is recommended to consult the current Safety Data Sheet for precautions and safety before starting processing.

The Safety Data Sheet is available at www.mysds.henkel. Information for allergy sufferers on Tel. 0049 (0)211 797 0 (keyword emergency)



The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Henkel AG & Co. KGaA

Henkelstr. 67, D-40589 Düsseldorf, P.O. Box, D-40191 Düsseldorf
Phone: +49 (0) 211 / 797-0
Internet: www.prittworld.com

