

## TECHNOMELT CLEANER PURE

February 2017

#### PRODUCT DESCRIPTION

TECHNOMELT CLEANER PURE provides the following product characteristics:

Technology	Cold cleaning agent
Product Type	Cleaning agent
Appearance	Clear light yellow liquid

#### **Application Areas**

Cleaning of machine surfaces, application units and general machinery, specially to remove residual adhesive and heavy grease and grime.

#### **Product Properties**

Cleaning agent based on natural resources for the application at room temperature.

#### **Technical Data**

#### **TECHNOMELT CLEANER PURE:**

Typical Properties	
Density, g/ml @ 20 °C,	0.95
DIN 51757	
pH value	3.7
Viscosity, mPas	5 to 40

# DIRECTIONS OF USE Preliminary Statement

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

#### **Application**

- Recommended working temperature: application at room temperature
- Shake well before use to provide equal viscosity.
- Carefully spray affected area and allow to react for a few minutes.
- Carefully remove with cloth and if necessary repeat procedure.
- Please observe EG-Safety Data Sheet.
- Can be applied manually or by using an airless spraying system.
- Due to its viscosity TECHNOMELT CLEANER PURE can also be used on vertical sufaces.

#### **Handling Information**

- · Before use check if materials are suitable.
- Do not spray on hot surfaces.
- Not suitable for the cleaning of plexiglas.

#### **STORAGE**

When stored in a dry and cool place in the original unopened containers shelf life is as follows.

Optimum storage temperature: 5 - 30 °C.

#### Shelf life:

Shelf-life (in unopened original packaging), months 36

#### Classification:

Please refer to the corresponding safety data sheets for details on:

Hazardous Information Transport Regulations Safety Regulations



### **ADDITIONAL INFORMATION**

#### Disclaimer

#### Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

and Henkel France SA please additionally note the following: In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage:** [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

Reference 0.2

Henkel AG & Co. KGaA 40191 Düsseldorf, Germany Phone: +49-211-797-0 Henkel Corporation Bridgewater, NJ 08807, USA Phone: +1-908-685-7000 Henkel (China) Co.Ltd. 201203 Shanghai, China Phone: +86-21-2891-8000

For more information contact us on www.henkel.com