

## TECHNOMELT® E-COM G10

February 2024

### Product description

TECHNOMELT® E-COM G10 provides the following product characteristics:

<b>Technology</b>	Synthetic Polymer
<b>Product type</b>	Hotmelt
<b>Application</b>	Packaging industry
<b>Appearance</b>	Pale white chubs

### Application areas

- Bonding of dense papers for different packaging applications

### Technical data

#### TECHNOMELT® E-COM G10:

Viscosity, Brookfield - 150 °C, mPa.s (cP) 6000 to 9000

Softening point, mettler, °C ~95

### Performance properties

Open time Medium

### Directions for use

#### Preliminary statement

Prior to use it is necessary to read the **Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

#### Application method

Application method:

- wheel
- spray
- slot nozzle
- random fiberization method

#### Working temperature

Recommended working temperature 150 to 200 °C

#### Cleaning

For the cleaning of melting tanks and application systems, we recommend the use of our HOTMELT CLEANER Q1924.

For the cold cleaning of surface soiling on application equipment, conveyor belts or other machine parts, TECHNOMELT CLEANER MELT-O-CLEAN can be applied.

During use, please follow the safety instructions.

#### Handling information

Due to the variety of substrates available, adhesion of materials can be very different. Therefore pre-tests should be carried out. See also "General Instructions for the Application of Hotmelts". Material is applied hot. Appropriate clothing and eye protection should be used. Use with adequate ventilation to remove any hotmelt fumes or vapours that are generated. Keep containers and pre-melters covered to avoid contamination.

#### Storage

Rotate stock, using oldest material first.

Do not mix with other adhesives.

When stored in a dry and cool place in the original unopened packaging shelf life is as follows:

#### Shelf life

Shelf-life (in unopened original packaging), months 24

Refer to expiry date on original packaging.

#### Classification:

Please refer to the corresponding **Safety Data Sheet** for details on:

**Hazardous Information**

**Transport Regulations**

**Safety Regulations**



## Additional information

### Disclaimer

The information provided in this Technical data sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical data sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

### Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 4